

H2600A 规格书(Line-up)

基板 CCL: H2600A

1、CCL: H2600A

Core Thickness		Standard Construction	Copper Foil		Notes
mm	mil		Thickness	Type	
0.70	28.0	7628X2+毛毡 X1	H/H	HTE	含铜
0.75	29.5	7628X2+毛毡 X1	0/0	HTE	不含铜
0.80	31.0	7628X2+毛毡 X1	1/0、H/0	HTE	含铜
0.86	34.0	7628X2+毛毡 X1	H/0	HTE	含铜
0.90	31.0	7628X2+毛毡 X1	H/H	HTE	含铜
1.00	39.0	7628X2+毛毡 X2	1/0、1/1	HTE	含铜
1.00	39.0	7628X2+毛毡 X1	2/2	HTE	含铜
1.10	43.0	7628X2+毛毡 X2	H/H	HTE	含铜
1.20	47.0	7628X2+毛毡 X2	1/0、1/1	HTE	含铜
1.50	59.0	7628X2+毛毡 X3	H/H、H/0、1/1 1.5/0、1.5/1.5、2/2	HTE	含铜
1.60	63.0	7628X2+毛毡 X3	H/H、1/1	HTE	含铜
1.70	67.0	7628X2+毛毡 X4	H/H	HTE	含铜

Remark: 1. The above data is for your reference only.

2. Please contact WAZAM sale and TS team if need more Laminates type.